



400 Spring Street • Royersford, PA 19468 USA



STRAINERS

Part No.	Suction Strainer, Plated Steel	Ship Wt. (Lbs.)
C360-90	1" Suction Strainer with 1/4" Openings	2
C229-90	1-1/2" Suction Strainer with 3/8" Openings	2
C230-90	2" Suction Strainer with 3/8" Openings	3
C362-90	2" Suction Strainer with 1" Openings	2
C387-90	2-1/2" Suction Strainer with 1/16" Opening	4
C519-90	3" Suction Strainer with 3/8" Openings	4
C520-90	3" Suction Strainer with 1-1/2" Openings	4
C364-90	4" Suction Strainer with 1-1/2" Openings	4
C377-90	6" Suction Strainer with 2-1/2" Openings	6
C210-90	2" BSPT Suction Strainer with 3/8" Openings	3
C211-90	2" BSPT Suction Strainer with 1" Openings	3
C310-90	3" BSPT Suction Strainer with 3/8" Openings	4
C311-90	2" BSPT Suction Strainer with 1-1/2" Openings	4

Constructed of Plated Steel for both Standard and Trash Types. Available in 1" to 6" sizes to fit either Standard or Trash Types.

NIPPLE KITS

Part No.	Nipple Kits: Include 2 Nipples and Thread Sealant in Single Carton	Ship Wt. (Lbs.)
C365-90	1-1/2" NPT x NPT Pipe Nipple Kit	2
C366-90	2" NPT x NPT Pipe Nipple Kit	2
C367-90	3" NPT x NPT Pipe Nipple Kit	4
C368-90	4" NPT x NPT Pipe Nipple Kit	6
C369-90	2" NPT x BSPT Pipe Nipple Kit	2
C370-90	3" NPT x BSPT Pipe Nipple Kit	4
C371-90	4" NPT x BSPT Pipe Nipple Kit	6

Nipple Kits are available in both NPT x NPT and NPT x BSPT. Machined nipple faces for positive seal to hose gasket. Each Nipple Kit includes two nipples and thread sealant packed in single carton.

FOOT VALVES

Part No.	Foot Valve	Ship Wt. (Lbs.)
C378-90	4 for 1: Fits Pipe Sizes 3/4", 1", 1-1/4" and 1-1/2"	2
C379-90	2"	2

Foot Valves are available in 2" or 4 for 1.

FIRE HOSE NOZZLES

Adjustable Fire Hose Nozzle Size (NPSH)	Part No.	Length	Handles Up to (GPM)	Ship Wt. (Lbs.)
1"	C332-90	4-5/8"	22	2
1-1/2"	C334-90	4-3/4"	75	2
2"	C336-90	4-3/4"	75	2

The Red Lexan Fire Hose Nozzle is designed for water service applications that require high pressure and/or commercial and industrial applications. Adjustable spray, fog and straight streams. Temperature Range 10°F to 150°F.

FIRE PUMP ADAPTER

Part No.	Fire Pump Adapter	Ship Wt. (Lbs.)
C231-90	2.5" NPT X 2.5" NH/NST Male Threaded Adapter	2

Hose adapter Male x Male threaded to convert 2.5" NPT to 2.5" NH (National Hose Thread) for use with American standard fire hose coupling/connection.

ADJUSTABLE SPANNER/HYDRANT WRENCH

Part No.	Adjustable Wrench	Ship Wt. (Lbs.)
C340-90	1-1/2" – 6" Adjustable Spanner/Hydrant Wrench	5

Heavy duty adjustable hydrant wrench suitable for rocker lug or pin couplings from 1-1/2" up to 6".



Manufacturer of AMT & IPT Pumps

400 Spring Street • Royersford, PA 19468 USA



